



Cruiser SE+ 3MP

3MP H.265 Wi-Fi P&T Camera

Cruiser SE+ 3MP delivers 3MP live monitoring with a choice of 3.6 mm lens option, With 3MP live monitoring and 0~355° pan & 0~90° tilt features, Cruiser SE+ 3MP ensures every corner of your home completely covered. It supports four night vision modes for clear-as day clarity even in pitch dark. With IP66 certified, the camera can be used outdoors under different weather conditions.





Human Detection

Quickly find human targets in you home



Smart Tracking

Automatically tracks moving objects



Active Deterrence

Scare away unwelcome visitors with built-in spotlight and 110dB security siren



IP66

Weatherproof from dust and water



Two-way Talk

Real-time communicate with people at the camera



Diversified Storage

Supports NVR, Cloud Storage or Micro SD card (up to 512 GB)



Alarm Notification

Sends instant motion-activated alerts to your mobile phone



Wi-Fi Connection

IEEE802.11b/g/n/ax support Wi-Fi 6



Smart Color Night Vision

Support four-mode night vision for clear-as day clarity even in pitch dark



Stay close with what you care

With Cloud service, you will have access to what you care as long as Internet is available. You can record daily or motion videos on Cloud and play back anytime anywhere.



Specifications

Camera

1/2.8" 3 Megapixel Progressive CMOS

3 MP(2304*1296)

Night Vision: 30m(98ft) Distance

3.6 mm Fixed Lens

Field of View: 82° (H), 44° (V), 104° (D)

355° Pan & 0~90° Tilt

Video & Audio

Video Compression: H.265/H.264

20 fps Frame Rate 8x Digital Zoom

Built-in Mic & Speaker, 110dB Siren

Built-in Spotlight

Notice Management

Motion Detection

Human Detection

What's in the box

- 1x Camera
- 1x Quick Start Guide
- 1x Power Adapter
- 1x Installation Position Map
- 1x Mounting Bracket
- 1x Waterproof Connector
- 1x Screw package

Network

1 x 100Mbps Ethernet Port Wi-Fi:IEEE802.11b/g/n/ax Imou App: iOS, Android ONVIF

Auxiliary Interface

Micro SD Card Slot (up to 512 GB) Reset Button

General

DC 12V 0.5A Power Supply Power Consumption:<6 W

Material: Plastic

Working Environment:-30° C \sim +50° C, Less Than 95%RH Dimensions: 121 \times 136 \times 183 mm (4.76 \times 5.35 \times 7.2 inch)

Weight: 405 g (0.89 lb)

IP66

