



- › Generator Starting Function
- › PWM or MPPT Option
- › Selectable input voltage range
- › Fast set up
- › Compatible to different AC sources
- › Overload and short circuit protection
- › Cold start function
- › Optional anti-dust kit



MODEL	TT-NEW1K	TT-NEW1K/MPPT	TT-NEW3K	TT-NEW3K/MPPT	TT-NEW5K	TT-NEW5K/MPPT
Rated Power [VA/W]	1000/1000		3000 / 3000		5000 / 5000	
Parallel Capability	No					
<b>INPUT</b>						
Voltage [V AC]	230					
Selectable Voltage Range [V AC]	170-280 (For Personal Computers) ; 90-280 (For Home Appliances)					
Frequency Range [Hz]	50 / 60 (Auto Sensing)					
<b>OUTPUT</b>						
AC Voltage Regulation (Batt. Mode) [V AC]	230 ± 5%					
Surge Power [VA]	2000		6000		10000	
Efficiency (Peak) [%]	90 ~ 93					
Transfer Time [ms]	10 (For Personal Computers) ; 20 (For Home Appliances)					
Waveform	Pure Sine Wave					
<b>BATTERY</b>						
Battery Voltage [V DC]	12		24		48	
Floating Charge Voltage [V DC]	13.5		27		54	
Overcharge Protection [V DC]	16		33		63	
<b>SOLAR CHARGER &amp; AC CHARGER</b>						
Solar Charger Type	PWM	MPPT	PWM	MPPT	PWM	MPPT
Max. PV Array Open Circuit Voltage [V DC]	55	102	80	102	105	145
Max. PV Array Power [W]	600	500	1200	1000	2400	3000
MPPT Range @ Operating Voltage [V DC]	N/A	17 ~ 80	N/A	30 ~ 80	N/A	60 ~ 115
Max. Solar Charge Current [A]	50	40	50	40	50	60
Max. AC Charge Current [A]	20		25		60	
Max. Charge Current [A]	50	60	70	60	110	120
<b>PHYSICAL FEATURES</b>						
Dimension, D x W x H [mm]	88 x 225 x 320		100 x 285 x 334		100 x 300 x 440	
Net Weight [kg]	4.4	4.5	6.3	6.5	8.5	9.7
Communication Interface	USB/RS232					
<b>ENVIRONMENT</b>						
Humidity [%]	5 to 95 Relative Humidity (Non-condensing)					
Operating Temperature [°C]	-10 ~ 50					
Storage Temperature [°C]	-15 ~ 60					

\* TommaTech GmbH reserves the right to change the specification of products without prior notice.