


10/100/1000M Cloud PoE Switch

EW-ES3006CG-AP | EW-ES3010CG-AP | EW-ES3020CG-AP | EW-ES3028CG-AP



Overview

EWIND Cloud Smart PoE Switch Series features an advanced remote online management platform designed to deliver quick responses and versatile capabilities. Key features include PoE scheduling, PoE auto-alive check, port settings, alarm notifications, VLAN configuration, and topology mapping etc. These functionalities enable users to manage their networks with ease, ensuring optimal performance, enhanced productivity, and an improved user experience. With the EWIND Cloud App/Website Platform, users can monitor and maintain their network and security systems anytime, anywhere.

Key Features

- Supports EWIND remote cloud platform management and mobile app operation, offering various real-time alerts notifications, fault detection and port restart etc;
- Supports software updates, reserves customization options, and provides a reset function;
- Discovers devices using the ONVIF protocol to display a cloud-based topology map of connected PDs;
- Support IEEE802.3at/af standard, PoE Power up to 30W for each PoE port;
- Plug and Play, easy to setup.
- Built-in Advanced PoE and Power supply to Empower Surveillance.


Highlights

EWIND Cloud PoE Switches integrate seamlessly with the EWIND Cloud platform / Mobile APP, enabling remote management of your devices through a secure, cloud-based interface. The platforms automatically generates a network topology, allowing you to efficiently monitor and manage your entire CCTV system while quickly identifying network issues in real time. This enhances operational efficiency and significantly simplifies network maintenance.



Topology Management & Remote Maintenance

EWIND Cloud offers a robust, cloud-based service system that provides comprehensive management of on-site devices, ensuring seamless connectivity and offering a full suite of support services. Additionally, the Cloud PoE Switches are equipped with a long-distance PoE functionality, capable of delivering power to devices up to 300 meters away. It is suitable for a variety of applications, including small to medium-sized businesses (SMBs), CCTV security systems, and environments such as homes, factories, and offices.



Specifications

Product Picture				
Model	EW-ES3006CG-AP	EW-ES3010CG-AP	EW-ES3020CG-AP	EW-ES3028CG-AP
Ports	4x1000M RJ45 PoE ports	8x1000M RJ45 PoE ports	16x1000M RJ45 PoE ports	24x1000M RJ45 PoE ports
Uplink Ports	1x1000M RJ45 port 1x1000M SFP Fiber port	1x1000M RJ45 port 1x1000M SFP Fiber port	2x1000M RJ45 ports 2x1000M SFP Fiber ports	2x1000M RJ45 ports 2x1000M SFP Fiber ports
PoE Ports	Port 1-4	Port 1-8	Port 1-16	Port 1-24
PoE Standards	IEEE 802.3af/at	IEEE 802.3af/at	IEEE 802.3af/at	IEEE 802.3af/at
Network Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z IEEE 802.3x	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z IEEE 802.3x	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z IEEE 802.3x	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z IEEE 802.3x
Max / Average PoE Power	15.4W/30W per Port	15.4W/30W per Port	15.4W/30W per Port	15.4W/30W per Port
Total Power Budget	65W	120W	300W	400W
PoE Pin Assignment	1, 2(+)/3, 6(-)			
Forwarding Mode	Store and Forward			
Switching Capacity	12Gbps	20Gbps	40Gbps	56Gbps
Forwarding Rate	11.7Mpps	19.5Mpps	29.76Mpps	41.66Mpps
MAC Table	2K	2K	8K	16K
Buffer Memory	1M	1M	4M	4M
Power Supply	Built-in power supply, AC 100~240V 50/60HZ			
Dimension	195*130*40MM	220*145*40MM	440*190*44MM	440*190*44MM
Operation Temp / Humidity	-20°C to +55°C; 5%~90% RH non condensing			
Storage Temp / Humidity	-40°C to +75°C; 5%~95% RH non condensing			
Net /Gross Weight	<0.85kg / <1kg	<1.1kg / <1.3kg	<2.8kg / <3kg	<4.4kg / <4.6kg
Installation Methods	Desktop	Desktop	Desktop / Rack-Mounted	Desktop / Rack-Mounted
Protections	IEC61000-4-2(ESD): ±8kV contact discharge, ±15kV air discharge IEC61000-4-5(Lightning protection/ Surge): Power:CM±4kV/DM±2kV; Port: ±4kV			
Protection Level	IP30			
Certifications	CCC; CE mark, commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS			
Warranty	3-Year	3-Year	3-Year	3-Year

Ordering Information

Model	Products	PoE Ports	Uplink Ports	Total PoE Budget
EW-ES3006CG-AP	4-Port Gigabit Cloud Smart PoE Switch	4	1x1000M RJ45 1x1000M SFP	65W
EW-ES3010CG-AP	8-Port Gigabit Cloud Smart PoE Switch	8	1x1000M RJ45 1x1000M SFP	120W
EW-ES3020CG-AP	16-Port Gigabit Cloud Smart PoE Switch	16	2x1000M RJ45 2x1000M SFP	300W
EW-ES3028CG-AP	24-Port Gigabit Cloud Smart PoE Switch	24	2x1000M RJ45 2x1000M SFP	400W

Packaging Information

CONTENT	QTY	UNIT
4/8/16/24 Port Gigabit Cloud Managed PoE Switch	1	SET
AC Power Cord	1	PC
Rack Mounting Ears (16/24-Port Model)	1	PAIR
User Guide	1	PC
Warranty Card	1	PC



EWIND Technology Co., Limited.

Office Address: Room 508, 5/F, XingHe World Tower E, Yabao Road, Longhua Dist, Shenzhen City, Guangdong, China.

Factory Address: 301, Blk 2, 4/F, West Ln 1, Dabao Rd, 33 Area, Shanghe Community, Xin'an Sub-Dist, Bao'an Dist, Shenzhen City, Guangdong, China.

Website: www.ewindnet.com

Email: info@ewindnet.com

Tel: +86-755-2100 6440

